

DEEP CYCLE LiFePO4 BATTERY

12.8V 200Ah

2560Wh



PRODUCT SPECIFICATION

Nominal Characteristics

Rated Capacity	200Ah (Typ.) / 200Ah (Min.)
Nominal Voltage	12.8V

* Standard Charge and Standard Discharge.

Charge Characteristics

End Of Charge Voltage	14.4V
Charge Mode	CC / CV
Charging Current (Charger Charging Current)	0.2C
Charging Cut-off Current	0.02C
Charging Time	5~6h
Max Continuous Charge Current	200A

Discharge Characteristics

Max Continuous Discharging Current	200A
Instantaneous Current	600A (3s Duration)

Protection Thresholds

Over-Charge Voltage Protection (cell)	3.65V (±0.05V)
Over-Discharge Voltage Protection (cell)	2.3V (±0.1V)
Over-Current Discharge Protection	1000A (±200A)
Temperature Protection	Battery Charging: 70±5°C Battery Discharge: 70±5°C MOS: 105±5°C

Environmental Conditions

Operation Temperature Range	Charge	0~45°C
	Discharge	-20~60°C
Storage Temperature Range	≤3 Month	-20~45°C
	≤1 Year	-20~20°C

* 60±25%R.H. at the shipment state

Cell Dimensions

Cell Dimension(L*W*H) (mm)	169.9*388.7*239.5(±3)
----------------------------	-----------------------

Cycle Life

Charge	0.2C to 14.6V
Cut-off voltage to 0.02C	Rest Time : 10min
Discharge	0.2C to 10V
Rest Time	10min
Temperature	25±5°C

* Capacity retention ≥80% after 2,000 cycles.

Mode of use

Max Support	4 Set 12.8V Batteries in Series
-------------	---------------------------------